



## Broken Line

Azerbaijan is famous for its carpets. As a master carpet designer you want to make a new design by drawing a **broken line**. A broken line is a sequence of  $t$  line segments in a two-dimensional plane, which is defined by a sequence of  $t + 1$  points  $p_0, \dots, p_t$  as follows. For each  $0 \leq i \leq t - 1$  there is a segment connecting points  $p_i$  and  $p_{i+1}$ .

In order to make the new design, you have already marked  $n$  **dots** in a two-dimensional plane. The coordinates of dot  $i$  ( $1 \leq i \leq n$ ) are  $(x[i], y[i])$ . **No two dots have the same x or the same y coordinate**.

You now want to find a sequence of points  $(sx[0], sy[0]), (sx[1], sy[1]), \dots, (sx[k], sy[k])$ , which defines a broken line that

- starts at  $(0, 0)$  (that is,  $sx[0] = 0$  and  $sy[0] = 0$ ),
  - contains all of the dots (not necessarily as the endpoints of the segments), and
  - consists solely of horizontal or vertical segments (two consecutive points defining the segment).
- (broken line have an equal x or y coordinate)

The broken line is allowed to intersect or overlap itself in any way. Formally, each point of the plane may belong to any number of segments of the broken line.

This is an output-only task with partial scoring. You are given 10 input files specifying the locations of dots. For each input file, you should submit an output file describing a broken line with the required properties. For each output file that describes a valid broken line your score depends on the **number of segments** in the broken line.

You are not supposed to submit any source code for this task.

## Input format

Each input file is in the following format

$n$  : 1 line •  
 $x[i] \ y[i]$  : ( $1 \leq i \leq n$  line  $1 + i$ ) (for •

## Output format

Each output file must be in the following format

$k$  :1 line •  
 $sx[i] \ sy[i] : (1 \leq i \leq k$  line  $1 + i$  (for •

Note that the second line should contain  $sx[1]$  and  $sy[1]$  (i.e., the output **should not** contain  $sx[0]$  and  $sy[0]$ ). Each  $sx[i]$  and  $sy[i]$  should be an integer


## Example

:For the sample input

```
4
2 1
3 3
4 4
5 2
```

:a possible valid output is

```
6
2 0
2 3
5 3
5 2
4 2
4 4
```



.Please note this example is not among the actual inputs of this task

## Constraints

- $1 \leq n \leq 100\,000$
- $1 \leq x[i], y[i] \leq 10^9$
- .All values of  $x[i]$  and  $y[i]$  are integers
- No two dots have the same  $x$  or the same  $y$  coordinates, i.e.  $x[i] \neq x[j]$  **and**  $y[i] \neq y[j]$
- $i \neq j$  for
- $-2 \cdot 10^9 \leq sx[i], sy[i] \leq 2 \cdot 10^9$
- .The size of each submitted file (either an output or a zipped file) cannot exceed 15MB

## Scoring

For each test case, you can get up to 10 points. Your output for a test case will get 0 points if it does not specify a broken line with the required properties. Otherwise, the score will be determined using a decreasing sequence  $c_1, \dots, c_{10}$ , which varies by testcase

Assume that your solution is a valid broken line consisting of  $k$  segments. Then, you will get

- $(1 \leq i \leq 10 \text{ points, if } k = c_i \text{ (for } i$
- $(1 \leq i \leq 9 \text{ points, if } c_{i+1} < k < c_i \text{ (for } i + \frac{c_i - k}{c_i - c_{i+1}}$
- $, k > c_1 \text{ points, if } 0$
- $.k < c_{10} \text{ points, if } 10$

.The sequence  $c_1, \dots, c_{10}$  for each testcase is given below

Testcases	01	02	03	04	05	06	07-10
$n$	20	600	5 000	50 000	72 018	91 891	100 000
$c_1$	50	1 200	10 000	100 000	144 036	183 782	200 000
$c_2$	45	937	7 607	75 336	108 430	138 292	150 475
$c_3$	40	674	5 213	50 671	72 824	92 801	100 949
$c_4$	37	651	5 125	50 359	72 446	92 371	100 500
$c_5$	35	640	5 081	50 203	72 257	92 156	100 275
$c_6$	33	628	5 037	50 047	72 067	91 941	100 050
$c_7$	28	616	5 020	50 025	72 044	91 918	100 027
$c_8$	26	610	5 012	50 014	72 033	91 906	100 015
$c_9$	25	607	5 008	50 009	72 027	91 900	100 009
$c_{10}$	23	603	5 003	50 003	72 021	91 894	100 003

## Visualizer

In the attachments of this task, there is a script that allows you to visualize input and output .files

:To visualize an input file, use the following command

```
python vis.py [input file]
```

You can also visualize your solution for some input, using the following command. Due to technical limitations, the provided visualizer shows only **the first 1000 segments** of the .output file

```
python vis.py [input file] --solution [output file]
```

:Example

```
python vis.py examples/00.in --solution examples/00.out
```